## (19) World Intellectual Property **Organization**

International Bureau





(43) International Publication Date 31 March 2005 (31.03.2005)

**PCT** 

## (10) International Publication Number WO 2005/028370 A1

(51) International Patent Classification7:

C01G 33/00

(21) International Application Number:

PCT/BR2004/000003

- (22) International Filing Date: 23 January 2004 (23.01.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

PI 0304252-9

25 September 2003 (25.09.2003)

- (71) Applicants (for all designated States except US): COMPANHIA BRASILEIRA DE METALURGIA E MINERAÇÃO [BR/BR]; Rua Pequetita, 111, 04552-902 Sã Paulo-SP (BR). IPT-INSTITUTO DE PESQUISAS TECNOLÓGICAS DO ESTADO DE SÃO PAULO S/A [BR/BR]; Cidade Universitária "Armando de Salles Oliveira", 05508-901 São Paulo-SP (BR).
- (72) Inventors; and
- Inventors/Applicants (for US only): TAGUSAGAWA, Solon, Yasuhiko [BR/BR]; Rua Engenheiro Afonso Bauer, 104, 05616-080 São Paulo - SP (BR). ONO, Alberto, Akikazu [BR/BR]; Rua das Avencas, 120, 38182-194 Araxá - MG (BR). BENEDUCE, Flávio, Neto [BR/BR]; Rua Porto Rico, 95, 01436-100 São Paulo - SP (BR).

FERREIRA, João, Batista, Neto [BR/BR]; Rua Fernão Dias, 264, Apto. 21, 05427-000 São Paulo - SP (BR).

- (74) Agent: MOMSEN, LEONARDOS & CIA.; Rua Teofilo Otoni 63, 10th floor, 20090-080 Rio de Janeiro - RJ (BR).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A PROCESS FOR THE PRODUCTION OF NIOBIUM OXIDE POWER FOR USE IN CAPACITORS

(57) Abstract: The present invention is related to a process for the production of a powder of niobium monoxide (NbO) having a high purity, large specific surface area, controlled oxygen and nitrogen contents and a morphology adequate for use in the manufacture of capacitors, characterized by comprising two niobium pentoxide (Nb<sub>2</sub>O<sub>5</sub>) reduction steps, the first step comprising reducing, by hydrogen, the niobium pentoxide (Nb<sub>2</sub>O<sub>5</sub>) to niobium dioxide (NbO<sub>2</sub>), and the second step comprising reducing niobium dioxide (NbO<sub>2</sub>) to niobium monoxide (NbO), by using an oxygen getter material in a convenient atmosphere which permits the transfer of the oxygen atoms from the niobium oxide (NbO<sub>2</sub>) to the getter material, under adequate conditions of time and temperature to form the niobium monoxide (NbO). The particles of powder of niobium monoxide (NbO) produced using the instant process are small, have a large surface area and an appropriate morphology, and are adequate for the production of capacitors.

